

Time (sec)	Boost (PSI)	Calculated	Fine WGDC	Ign. Advanc	Inj. Duty	Cy Knock	Sum LTFT	Used	Learned	Kn
0	-1.39	258	0	29	11.72	0	5.86	100		
0.087	-0.96	291	0	28	12.66	0	5.86	100		
0.176	0.3	312	20.5	24	14.36	0	5.86	100		
0.284	0.83	318	25.5	23	14.96	0	5.86	100		
0.378	1.65	372	64	20	15.83	0	5.86	100		
0.453	3.59	381	71	14	17.34	0	5.86	100		
0.54	4.56	381	72	12	17.89	0	5.86	100		
0.623	5.67	405	74.5	11	23.18	0	5.86	100		
0.71	7.12	411	89	6	24.84	0	5.86	100		
0.799	8.57	429	100	4	27.93	0	5.86	100		
0.873	10.12	432	100	4	29.12	0	0	100		
0.959	11.96	432	100	4	30.77	0	0	100		
1.044	13.89	435	100	3	34.4	0	0	100		
1.147	16.07	435	100	3	40.81	0	0	100		
1.248	19.07	438	100	3	45.41	0	0	100		
1.322	21.53	438	100	3	49.46	0	0	100		
1.417	22.84	441	100	3	50.77	0	0	100		
1.501	23.32	441	100	3	50.7	0	0	100		
1.586	23.28	444	100	4	50.46	0	0	100		
1.672	22.79	447	100	5	50.03	0	0	100		
1.76	22.16	450	100	5	49.23	0	0	100		
1.849	21.58	450	100	5	50.14	0	0	100		
1.927	21.34	453	100	6	50.74	0	0	100		
2.026	21.15	453	100	6	52.68	0	0	100		
2.104	21.05	450	100	6	53.3	0	0	100		
2.202	21.15	447	100	6	55.21	0	0	100		
2.29	21.24	447	100	7	57.28	0	0	100		
2.362	21.49	444	100	7	58.77	0	0	100		
2.449	21.78	441	100	7	60.68	0	0	100		
2.533	22.07	441	100	6	62.71	0	0	100		
2.628	22.11	438	100	6	64.59	0	0	100		
2.701	22.6	435	100	6	65.21	0	0	100		
2.783	22.45	435	100	6	65.84	0	0	100		
2.866	22.5	432	100	7	65.89	0	0	100		
2.956	22.21	432	100	8	66.07	0	0	100		
3.034	22.02	429	100	8	66	0	0	100		
3.125	21.68	426	100	8	65.95	0	0	100		
3.204	21.34	423	100	8	66.59	0	0	100		
3.302	20.91	423	100	8	66.1	0	0	100		
3.385	20.42	420	100	8	66.33	0	0	100		
3.478	20.08	417	100	10	65.52	0	0	100		
3.55	19.79	417	100	10	65.3	0	0	100		
3.638	19.21	414	100	10	65.06	0	0	100		
3.72	19.02	411	100	10	64.86	0	0	100		
3.798	18.63	411	100	10	64.64	0	0	100		
3.88	18.39	408	100	10	65.22	0	0	100		
3.966	18.24	405	100	10	65.81	0	0	100		
4.052	18.15	405	100	10	66.6	0	0	100		
4.124	17.95	402	100	10	67.35	0	0	100		

4.203	17.95	399	100	10	68.14	0	0	100
4.291	17.95	399	100	10	68.82	0	0	100
4.363	18	396	100	10	69.47	0	0	100
4.451	17.95	396	100	10	69.83	0	0	100
4.523	17.95	393	100	10	70.65	0	0	100
4.61	18	390	100	10	71.01	0	0	100
4.682	18.15	390	100	10	72.15	0	0	100
4.77	18.2	387	100	10	72.97	0	0	100
4.857	18.2	384	100	10	73.71	0	0	100
4.951	18	381	100	11	74.36	0	0	100
5.036	18.05	381	100	10	75.18	1	0	100
5.126	18.1	378	100	10	76.43	1	0	100
5.227	17.95	375	100	10	77.26	1	0	100
5.315	17.81	375	100	10	77.92	1	0	100
5.412	17.95	369	100	10	78.04	1	0	100
5.496	17.81	366	100	10	78.32	1	0	100
5.59	17.71	360	100	10	78.71	1	0	100
5.674	17.18	255	68	10	72.77	1	0	100
5.783	8.62	132	18.5	18	7.82	1	0	100
5.86	-0.33	57	0	31	13.44	0	0	100
5.943	-6.18	15	0	40	8	0	5.86	100
6.025	-8.74	12	0	40	12.59	0	5.86	100
6.103	-9.52	12	0	40	11.97	0	5.86	100
6.186	-9.81	12	0	40	11.39	0	5.86	100
6.263	-10.1	12	0	40	11.2	0	5.86	100
6.351	-10.2	9	0	40	11.07	0	5.86	100

Load (load)	MAF	Voltage	RPM (RPM)	STFT (%)	Throttle Ar	WGDC Corr. (%)
74.69	2.6	2750	0.2	20	0	
79.38	2.79	2781	0.59	25	0	
88.75	2.8	2812	0.98	26	0	
95	2.83	2844	1.17	28	0	
105.31	3	2875	0.78	48	0	
116.88	3.15	2906	0.39	50	0	
117.5	3.14	2969	0	47	0	
131.88	3.25	3000	0	71	0	
139.69	3.3	3031	0	75	0	
150.62	3.49	3062	0	96	0	
155.94	3.48	3156	0	96	0	
162.19	3.57	3188	0	96	0	
175.31	3.73	3219	0	96	0	
198.12	3.75	3312	0	96	0	
217.81	3.82	3375	0	96	0	
232.5	3.82	3469	0	96	0	
236.25	3.89	3500	0	96	0	
232.81	3.89	3594	0	96	0	
228.12	3.87	3656	0	96	0	
221.56	3.76	3750	0	96	0	
216.25	3.83	3781	0	96	0	
214.69	3.83	3875	0	96	0	
214.38	3.96	3938	0	96	0	
215.62	3.82	4062	0	96	0	
216.25	4.02	4094	0	96	0	
219.06	3.92	4219	0	96	0	
222.5	3.94	4281	0	96	0	
225.94	4.17	4312	0	96	0	
227.19	3.95	4438	0	96	0	
233.12	4.18	4469	0	96	0	
234.38	4.3	4594	0	96	0	
234.69	4.27	4625	0	96	0	
232.19	4.05	4719	0	96	0	
229.06	4.26	4781	0	96	0	
225.62	3.97	4875	0	96	0	
222.5	3.96	4938	0	96	0	
221.56	3.98	4969	0	96	0	
217.19	4.26	5094	0	96	0	
213.12	4.14	5156	0	96	0	
209.38	4.18	5250	0	96	0	
206.25	4	5281	0	96	0	
202.81	4.13	5344	0	96	0	
199.69	4.23	5406	0	96	0	
197.5	4.01	5469	0	96	0	
194.69	4.18	5531	0	96	0	
193.75	4.21	5594	0	96	0	
194.38	4.28	5625	0	96	0	
193.44	4.21	5719	0	96	0	
194.69	4.17	5750	0	96	0	

194.38	4.25	5844	0	96	0
195.62	4.15	5875	0	96	0
194.69	4.32	5938	0	96	0
194.06	4.3	5969	0	96	0
195	4.29	6031	0	96	0
195	4.31	6062	0	96	0
195.31	4.2	6125	0	96	0
196.56	4.31	6188	0	95	0
196.25	4.28	6250	0	95	0
195.94	4.3	6312	0	94	0
196.56	4.27	6375	0	95	0
197.5	4.36	6438	0	95	0
197.81	4.35	6500	0	95	0
197.5	4.39	6562	0	94	0
195.94	4.32	6625	0	91	0
195.31	4.32	6656	0	90	0
194.06	4.39	6750	0	59	0
165	3.68	6750	0	29	0
115	3.16	6781	0	20	0
63.12	2.18	6719	0	10	0
32.19	1.64	6781	0	9	0
25	1.84	6719	0	9	0
22.19	2.02	6750	0	9	0
20	2.08	6750	0	9	0
19.06	2.15	6719	0	9	0
18.12	2.14	6750	0	9	0