

•ÈÀTime	Boost (PSI)	Fine WGDC R	Ign. Advance	Inj. Duty Cycl	Knock Sum (c	LTFT Used (%)
0	-6.42	0	35	4.95	0	0
0.14	-6.62	0	36	5	0	0
0.28	-6.52	0	36	4.93	0	0
0.42	-6.52	0	36	5.1	0	0
0.56	-5.75	0	34	6.58	0	0
0.7	-3.04	0	27	9.42	0	0
0.82	-0.23	26	21	11.33	0	0
0.96	0.2	32.5	20	11.62	0	0
1.08	0.88	40.5	17	12.21	0	0
1.22	1.41	52	14	12.81	0	0
1.34	2.33	66.5	13	13.32	0	0
1.48	3.15	66.5	13	14.41	0	0
1.6	4.22	66.5	12	15.4	0	0
1.74	5.19	66.5	11	18.72	0	0
1.86	6.59	66.5	8	22.66	0	0
2	7.99	66.5	7	24.81	0	0
2.12	9.73	66.5	5	28.26	0	0
2.26	11.67	66.5	4	31.34	0	0
2.38	13.99	66.5	3	36.57	0	0
2.52	16.65	67	3	40.4	0	0
2.66	19.31	67.5	2	44.61	0	0
2.78	21.49	67.5	2	47.31	1	0
2.92	22.11	67.5	2	48.23	1	0
3.06	22.11	68	2	48.2	1	0
3.2	21.87	68	3	50.16	0	0
3.32	22.07	68	4	52.62	0	0
3.46	22.21	68	4	55.19	0	0
3.58	21.68	68.5	5	56.75	0	0
3.72	21.58	68.5	5	58.85	0	0
3.84	21.2	69	6	59.25	0	0
3.98	21.49	69	6	60.51	0	0
4.1	21.34	69	6	61.65	0	0
4.24	21.2	69.5	8	62.99	0	0
4.38	21.15	69.5	7	64.78	0	0
4.52	21.24	69.5	8	66.39	0	0
4.66	21	69.5	8	67.56	0	0
4.8	20.86	69.5	9	69.39	0	0
4.92	20.66	70	9	69.52	0	0
5.06	20.86	70	9	72.23	0	0
5.18	21.49	70	9	73.85	0	0
5.32	21.53	70	8	75.45	0	0
5.44	21.63	70.5	9	76.32	0	0

5.58	21.49	70.5	9	78.59	0	0
5.7	21.34	70.5	10	79.9	0	0
5.84	20.95	70.5	10	77.24	0	0
5.96	20.81	70.5	10	78.19	0	0
6.1	20.57	70.5	10	82.5	0	0
6.24	20.42	71	11	79.16	0	0
6.36	19.94	71	11	83.14	1	0
6.5	19.55	71	11	83.64	0	0
6.62	19.16	71	11	83.81	0	0
6.76	18.92	71	11	83.96	0	0
6.88	18.73	71.5	13	81.16	0	0
7.02	18.44	71.5	13	80.57	0	0
7.14	18.24	71.5	13	81.5	0	0
7.28	17.91	71.5	13	85.67	0	0
7.4	17.62	72	13	85.9	0	0
7.56	17.37	72.5	13	86.65	0	0
7.68	17.28	73	13	87.48	0	0
7.82	17.08	73.5	13	87.25	0	0
7.96	16.94	73.5	13	84.92	1	0
8.1	16.7	74	13	88.72	0	0
8.24	12.63	11.5	-10	30.81	0	0
8.38	-2.99	0	0	15.88	0	0
8.52	-9.91	0	9	9.26	0	0
8.64	-11.21	0	18	0	0	0
8.78	-11.07	0	0	0	0	0
8.9	-10.78	0	0	0	0	0
9.04	-10.73	0	0	0	0	0
9.16	-10.73	0	0	0	0	0
9.3	-10.97	0	0	0	0	0
9.45	-11.02	0	0	0	0	0
9.58	-11.11	0	0	0	0	0

Load (load)	MAF Voltage	RPM (RPM)	STFT (%)	Throttle Angl	WGDC Corr. (%)
41.25	1.98	1964	0	8.09	0
40.94	2.02	1996	0	8.09	0
40.94	2.02	1988	-0.2	8.6	0
43.44	2.04	1996	-0.78	11.64	0
55.62	2.4	2023	0	16.69	0
75.94	2.72	2054	0	96.12	0
87.81	2.75	2101	0	97.13	0
93.12	2.74	2113	0	96.62	0
97.5	2.53	2144	0	96.62	0
101.56	2.94	2195	0	96.62	0
105.31	2.98	2257	0	97.13	0
110.62	3.02	2289	0	96.62	0
116.88	3.15	2324	0	96.62	0
132.5	2.81	2410	0	97.13	0
142.19	3.16	2488	0	96.62	0
154.06	3.33	2523	0	97.13	0
169.06	3.11	2585	0	96.62	0
181.25	3.66	2687	0	96.62	0
201.88	3.73	2761	0	96.62	0
221.25	3.82	2843	0	96.62	0
229.38	3.82	2964	0	97.13	0
232.81	3.64	3031	0	96.62	0
233.75	3.69	3152	0	96.62	0
232.81	3.87	3285	0	96.62	0
234.69	3.88	3371	0	96.62	0
234.69	3.9	3472	0	96.62	0
234.69	4.19	3597	0	96.62	0
238.75	4.31	3718	0	96.62	0
238.12	3.66	3863	0	96.62	0
235.31	3.76	3937	0	96.62	0
232.5	4.05	4046	0	96.62	0
230.31	3.98	4160	0	96.62	0
230.31	4.07	4277	0	96.62	0
231.25	4.13	4371	0	96.62	0
227.5	4.13	4507	0	96.12	0
228.44	4.09	4625	0	96.12	0
226.88	4.16	4742	0	96.12	0
225	4.15	4812	0	96.12	0
227.81	4.28	4945	0	96.62	0
227.19	4.23	5046	0	96.62	0
228.12	4.24	5156	0	96.62	0
227.81	4.32	5234	0	96.62	0

229.06	4.14	5332	0	96.62	0
230.31	4.25	5445	0	96.62	0
220.31	4.29	5527	0	96.12	0
217.81	4.23	5609	0	96.62	0
226.56	4.33	5726	0	96.62	0
224.69	4.3	5832	0	96.62	0
221.88	4.36	5902	0	96.62	0
220	4.34	6000	0	96.62	0
217.5	4.37	6093	0	96.12	0
211.25	4.4	6207	0	96.12	0
205.31	4.33	6265	0	96.62	0
210.62	4.4	6343	0	96.12	0
200.62	4.44	6437	0	96.62	0
205	4.43	6500	0	96.62	0
203.12	4.29	6597	0	96.62	0
201.88	4.32	6703	0	96.12	0
205	4.38	6781	0	95.61	0
204.06	4.39	6855	0	96.12	0
202.81	4.44	6937	0	96.62	0
201.88	4.44	7015	0	47.55	0
106.56	2.66	7054	0	15.68	0
40.31	1.89	6824	0	6.07	0
16.88	1.83	6488	0	4.05	0
11.56	1.78	6199	0	6.07	0
14.69	1.81	5925	0	6.07	0
14.69	1.78	5656	0	6.07	0
15.31	1.84	5394	0	5.06	0
15	1.76	5156	0	4.55	0
14.69	1.81	4925	0	4.55	0
14.69	1.8	4683	0	4.55	0
14.06	1.81	4449	0	4.05	0