

SPECIFICATIONS

FASTENER TIGHTENING SPECIFICATIONS

M1111003800280

ITEM	SPECIFICATION
Camshaft and valve stem seal	
Camshaft bearing cap bolt	20 ± 1 N·m (14 ± 0.5 ft-lb)
Camshaft position sensing cylinder bolt	22 ± 4 N·m (16 ± 3 ft-lb)
Camshaft position sensor support bolt	14 ± 1 N·m (120 ± 13 in-lb)
Camshaft position sensor support cover bolt	10 ± 2 N·m (89 ± 17 in-lb)
Camshaft sprocket bolt	89 ± 9 N·m (65 ± 7 ft-lb)
Control wiring harness bracket bolt	11 ± 1 N·m (98 ± 8 in-lb)
Ground terminal bolt (control wiring harness)	5.0 ± 1.0 N·m (44 ± 9 in-lb)
Heated oxygen sensor (front) bolt	10.5 ± 0.5 N·m (93 ± 4 in-lb)
Oil delivery body bolt	11 ± 1 N·m (98 ± 8 in-lb)
Rocker cover bolt	3.5 ± 0.5 N·m (31 ± 4 in-lb)
Rocker cover center cover bolt	3.0 ± 0.5 N·m (27 ± 4 in-lb)
Spark plug	25 ± 4 N·m (18 ± 3 ft-lb)
Vacuum pipe bolt	11 ± 1 N·m (98 ± 8 in-lb)
Vacuum pipe bracket bolt	11 ± 1 N·m (98 ± 8 in-lb)
Crankshaft oil seal	